WHEEL-BALANCERS - PASSENGERS' CARS

Integrated Sonar, Led light, Laser Line. BE FASTER and more productive!















www.giuliano-automotive.com

DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH LED DISPLAY.

LASER LINE AND LED LIGHT Complete with wheel guard, cones



Advanced software for further upgrades*.

LED display built into the weight holder.

Intuitive, Easy-to-use Control Panel.

USB port for firmware updating via PC/notebook.

FUNCTIONS -

- Automatic measuring of wheel diameter and distance
- Automatic START and STOP
- Static and dynamic balancing
- OPTIMATCH function
- · Self-diagnosis and Selfcalibration

LASER LINE

for exact positioning of adhesive weights.

LED LIGHT

to illuminate working area.





Automatic measuring of wheel width by SONAR (TW), standard.

SPECIAL ALU PROGRAM



Programs for selecting the best correction planes for any kind and shape of alloy rim.

SELF SELECTION MODE



Self-recognition of the Working program.



OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE

A very practical Wheel Lifter

reduces effort and increases

productivity (optional).





 Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel

(6 o'clock), easier and more accessible, by a Laser line indicator.

HIDDEN WEIGHT





*The performance of the machine over time can improve, thanks to targeted updates.

 Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website!

CTANDADD CEATURE

| SIANDAKD LEVINKES — | |
|--------------------------|------------------------------|
| Max. wheel weight | 75 kg |
| Max. wheel diameter | 1100 mm |
| Rim diameter | 10"-30" / 255-765 mm |
| Rim width | 1,5"-20" / 40-510 mm |
| Power supply | 230V 1ph (50/60) Hz |
| Unbalance detection time | 4,7 sec. (5 3/4"x14") 15 kg. |
| Balancing speed | < 150 rpm |
| Balancing precision | ÷ 1 g |
| Net weight with guard | 97 kg |
| Max. overall dimensions | 1350x1150x1280÷1540 mm |



- Wheel guard Set of 42-140 mm cones and quick clamping ring nut • Manual gauge for measuring wheel rim width
- Counterweight pliers SONAR TW