

Eye-catching graphics, updated software for a great user experience.

NEW
P54



P54

www.giuliano-automotive.com



DIGITAL ELECTRONIC 3-D WHEEL-BALANCER WITH VIDEO DISPLAY, LASER LINE AND LED LIGHT

✓ USB port for firmware updating via pen-drive.



Advanced software for further upgrades.*

✓ Flat screen HD color video monitor 19" TFT. Precise, reliable and easy to use software.

FUNCTIONS

- Automatic measuring of wheel diameter and distance.
- Automatic START and STOP.
- Static and dynamic balancing.
- OPTIMATCH function.
- Self-diagnosis and self-calibration.
- Optimization of static unbalance.
- CLIP system for application of stick-on weight.
- Complete with Wheel guard, cones and quick clamping ring nut.

LED LIGHT
to illuminate working area.


LASER LINE
for exact positioning of adhesive weights.

💡 A very practical **Wheel Lifter** reduces effort and increases productivity (optional).



✓ Automatic measuring of wheel width by **SONAR (TW)**, standard.

✓ SPECIAL ALU-S PROGRAMS



Programs for selecting the best correction planes for any kind and shape of alloy rim.

✓ SELF SELECTION MODE



Self-recognition of the Working program.

✓ HIDDEN WEIGHT



• Fast & Easy Split (FES) function, is really the fastest method on the market to split balancing weights behind the spokes of your aluminum wheel.

✓ OPPOSITE WEIGHT FUNCTION (OPF) WITH LASER LINE



• Laser Line function, enables to place the balancing stick-on weight on the lower inside part of the aluminum wheel (6 o'clock), easier and more accessible, by a Laser line indicator.

**The performance of the machine over time can improve, thanks to targeted updates.*

EXTENSIVE SELECTION OF STANDARD ACCESSORIES

OPTIONAL ACCESSORIES



- Wheel clamping adaptors
- Clamping cones with spacers
- Wheel lifter

Find out more on our website !

STANDARD FEATURES

Max. wheel weight	75 kg
Max. wheel diameter	1100 mm
Rim diameter	10"-30" / 255-765 mm
Rim width	1,5"-20" / 40-510 mm
Power supply	230V 1ph (50/60) Hz
Unbalance detection time	4,7 s (5 3/4"x14") 15 kg
Balancing speed	< 150 rpm
Balancing precision	÷ 1 g
Net weight with guard	104 Kg
Max. overall dimensions	1350x1150x1440+1540 mm

STANDARD ACCESSORIES



- Wheel guard
- Manual gauge for measuring wheel rim width
- Set of 42-140 mm cones and quick clamping ring nut
- Counterweight pliers
- **SONAR TW**